



your local global brand

# Gulf ATF DX III H

*Extra High Performance Automatic Transmission Fluid*

## Product Description:

**Gulf ATF DX III H** is an extra high performance automatic transmission fluid for all General Motors and Ford automatic transmissions requiring DEXRON®-III H specification) or MERCON® quality fluids respectively. The modern additive technology and specially selected base oils used in **Gulf ATF DX III H** provides superior thermo-oxidative stability, corrosion & rust protection, foam control, seal compatibility, friction durability and low temperature fluidity. **Gulf ATF DX III H** is designed to exceed the performance requirements of General Motors DEXRON®-III H and Ford MERCON® specifications.

**Gulf ATF DX III H** has superior thermo-oxidative stability, wear protection and resistance to chemical deterioration can provide longer fluid and component life, controlled frictional properties lead to smooth shift performance, efficient transmission of power and prevent shudder, extremely high Viscosity index ensures adequate lubrication in both high operating & low starting temperatures, provides excellent protection against rust and corrosion and effective foam control leads to smooth & lasting shift feel and reduces fluid loss, improved low temperature fluidity leads to easy pumping in the hydraulic circuits and better seal compatibility ensures longer seal life and reduces possibility of oil leakage.

**Gulf ATF DX III H** is recommended for & meets the warranty requirements of all vehicles of Ford requiring MERCON® quality fluids and General Motors requiring DEXRON®-III H quality fluids. Being back serviceable, also recommended for automatic transmissions requiring General Motors DEXRON® III , DEXRON®-II E or DEXRON®-II D fluids and also for imported cars like Audi, Honda, Mazda, Nissan, Opel, Renault, Toyota and Volkswagen where such fluids are specified.

### Meets the specifications of:

General Motors: DEXRON®-III H, Ford: MERCON®

### Approved by:

Volvo Transmission Oil 97341, ZF TE-ML-04D/14A

<u>Properties:</u>	<u>Test Methods:</u>	<u>Typical Values:</u>
Density @ 15°C	ASTM D4052	864 kg/m <sup>3</sup>
Kinematic Viscosity @ 40°C	ASTM D445	35.0 mm <sup>2</sup> /s (cSt)
Kinematic Viscosity @ 100°C	ASTM D445	7.3 mm <sup>2</sup> /s (cSt)
Brookfield Viscosity @ -40°C	ASTM D2983	<20000 mPa.s (cP)
Viscosity Index	ASTM D2270	170
Flash Point	ASTM D92	204°C
Pour Point	ASTM D97	-39°C
Colour	Visual	Red

Product Code: 2504

Date Issued: 22/06/2012

Date Superseded: 30/11/2011

Revision nr: 03