



your local global brand

Gulf Fork Oil 10

Suspension, Fork and Shock Absorber Oil

Product Description:

Gulf Fork Oil 10 is a blend of carefully selected paraffinic base oils and extremely effective inhibitor additives and has been designed for use in a wide variety of motorcycles and for different applications and climatic conditions. As the different motorcycle manufacturers require specific viscosities for fork oils, the **Gulf range** is available offered in a series of grades, from **Gulf Fork Oil 2.5** to **Gulf Fork Oil 10**. The very low pour point and high viscosity index contributes to the excellent performance of **Gulf Fork Oil 10** over a very wide temperature range; from freezing cold winter to very hot summer.

Gulf Fork Oil 10 exhibit an exceptional smooth hydraulic springing and shock absorbing action, while at the same time scuffing and wear are reduced to a minimum. **Gulf Fork Oil 10** offer good protection against foam and corrosion. Most importantly oil seal materials are not adversely affected by **Gulf Fork Oil 10**. The blend components used in **Gulf Fork Oil 10** are very resistant for thermal and oxidation stability, and the shear-stable polymers which provide the multi-grade viscosity characteristics ensure the oil stays 'in-grade' during prolonged periods of use. **Gulf Fork Oil 10** can be used in both cold and hot ambient temperatures and the smooth operation of the shock absorber/spring suspension system gives a safe and comfortable ride. **Gulf Fork Oil 10** exhibit minimal scuffing and wear and are compatible with oil seals. **Gulf Fork Oil 10** does not foam and protects against corrosion, and have durable stay-in-grade properties and may be mixed together to give the desired final viscosity indicated by the motorcycle or shock absorber manufacturer.

Gulf Fork Oil 10 is suitable for service fill use in the suspension forks of a large range of motorcycles, and can be used in competitions such as Motocross, Racing and Trials, as well as normal on-road service.

Meets the demands of many OEMs. Check the OEMs Manual for the right product.

Properties:

Density @ 20°C

Kinematic Viscosity @ 40°C

Kinematic Viscosity @ 100°C

Viscosity Index

Flash Point

Pour Point

Test Methods:

ASTM D4052

ASTM D445

ASTM D445

ASTM D2270

ASTM D92

ASTM D97

Typical Values:

862 kg/m³

32 mm²/s (cSt)

6.1 mm²/s (cSt)

141

204°C

-36°C

Product Code: 2402

Date Issued: 22/06/2012

Date Superseded: 02/12/2011

Revision nr: 02