



your local global brand

CVT Fluid

Automatic Transmission Fluid

Product Description

Gulf CVT Fluid is an ultra high performance transmission oil formulated with selected base stocks and specially recommended for use in the latest generations of Continuously Variable Transmission (CVT) - gearboxes which transfer traction via steel-made traction chains or push-belts.

Gulf CVT Fluid is based on exceptional quality synthetic base oil in combination with a special selected EP-additive package to reach to following properties:

- Good thermo-and oxidation.
- To be used in Audi Multitronic and/or Mercedes Benz Autotronic.
- Extended drain interval possible.
- Excellent antiwear, antirust and anticorrosion technology.
- High Viscosity index ensures adequate lubrication in both high operating & low starting temperatures.
- Better foam control leads to smooth & lasting shift feel and reduces fluid loss.
- Enhanced Low temperature fluidity assist in good cold start performance.
- Compatibility with all common seal materials.

Gulf CVT Fluid exceeds the following performance criteria

MB 236.20	Ford WSS M2C928A	Nissan NS-2	Toyota TC
VW G 052 180	BMW 83 22 0 136 376	BMW 83 22 0 429 154	

Typical Analysis

Properties	Unit	Method	Typical Value
Density @15°C	kg/m ³	ASTM D4052	848
Kin. Viscosity @40°C	mm ² /s	ASTM D445	34
Kin. Viscosity @100°C	mm ² /s	ASTM D445	7.0
Viscosity index		ASTM D2270	173
Brookfield Viscosity@-40°C	cP	ASTM D2983	11900
Flash Point COC, min	°C	ASTM D92	>201
Pour Point	°C	ASTM D97	-51
Foaming Tendency		ASTM D892	
Seq I			30/0
Seq II			30/0

Product Code: 2455	Date Issued: 31-12-2010	Date Reviewed: 15-08-2013	Revision:2
---------------------------	-------------------------	---------------------------	------------