



## Gulf Pride 2T Plus

### Semi-Synthetic, Low Smoke 2-Stroke Motorcycle Oil

#### Product Description

**Gulf Pride 2T Plus** is a premium quality semi-synthetic lubricant specially developed for high powered 2-stroke air cooled gasoline engines fitted with oil-injection or premix systems. It is formulated from premium quality base stocks, synthetic base fluid and unique performance additives for exceptional engine protection, cleanliness and low smoke in 2-stroke motorcycle/ scooter engines even under severe operating conditions. The product exceeds the latest international specifications of JASO FD, ISO-L-EGD & API TC and the requirements of leading global 2-stroke motorcycle/ scooter manufacturers.

#### Features & Benefits

- Outstanding lubricity protects against piston scuffing and premature wear of engine components
- Advanced formulation provides excellent control against engine deposits, exhaust system blocking and extended engine life without power loss
- Low ash additive technology prevents pre-ignition and spark plug fouling
- Specially selected synthetic base fluid reduces visible exhaust smoke
- Easy miscibility with gasoline ensures stable homogeneous mixture even at low ambient temperatures

#### Applications

- Recommended for high-powered 2-stroke motorcycles/ scooters operating under different conditions
- Suitable for both oil-injection and premix lubrication systems; follow manufacturer's recommendations for oil to fuel ratio
- Suitable for air cooled 2-stroke gasoline engines used in all terrain vehicles, lawn mowers and other applications requiring oils of this quality
- Also recommended for applications specifying ISO-L-EGC/ JASO FC or lower category oils for superior performance

#### Specifications, Approvals & Typical Properties

| Meets the following Specifications |             |                |
|------------------------------------|-------------|----------------|
| ISO-L-EGD                          |             |                |
| API TC                             |             |                |
| Has the following On File Status   |             |                |
| JASO FD                            |             |                |
| Typical Properties                 |             |                |
| Test Parameters                    | ASTM Method | Typical Values |
| Viscosity @ 100 °C, cSt            | D445        | 7.75           |
| Flash Point, °C                    | D 93        | 85             |
| Pour Point, °C                     | D 97        | -15            |
| TBN, mg KOH/g                      | D 2896      | 1.40           |
| Density @ 15°C, Kg/l               | D 1298      | 0.861          |
| Sulphated Ash, %wt                 | D 874       | 0.14           |

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

[www.gulfoilltd.com](http://www.gulfoilltd.com)