



your local global brand

Gulf Antifreeze

Antifreeze Concentrated Fluid

Product Description:

Gulf Antifreeze is a '*British-Standard Coolant*' composed of Mono Ethylene Glycol under addition of additives and free from nitrites, amines and phosphates to obtain good protection of all hard metals in the cooling system and engine. **Gulf Antifreeze** is neutral in relation to gaskets and hoses and has good resistance against foam and provides year-round frost and corrosion protection.

Gulf Antifreeze can be used throughout the year in all cooling systems in gasoline and diesel engines. Thanks to the balanced additive package and high quality Mono Ethylene Glycol, this standard quality antifreeze belongs to the highest quality in the market. Before use, **Gulf Antifreeze** needs be diluted in the recommended proportions with water. It is recommended to use at least 33 vol. % of **Gulf Antifreeze** in the coolant solution. This provides frost protection to -17°C. Concentrations higher than 70 vol. % are not recommended.

Gulf Antifreeze is recommended for use in cooling systems of all types of liquid cooled automotive and industrial internal combustion engines. Always refer to the OEM's manual for recommended coolant type!

Warning: Keep all antifreezes out of reach of children !!! Do not drink antifreeze !!!
If swallowed, induce vomiting and immediately call a doctor !!!

Meets the specifications of:

ASTM D3306/D4656, AFNOR NFR 15-601, BS 6580, CUNA NC 956-16, SAE J1034, UNE 26-361-88/1

<u>Properties:</u>	<u>Test Methods:</u>	<u>Typical Values:</u>
Density @ 20°C	ASTM D4052	1120 kg/m ³
Freezing Point @ 33% antifreeze & 67% water	ASTM D1177	-17°C
Freezing Point @ 50% antifreeze & 50% water	ASTM D1177	-35°C
Colour	Visual	Blue
pH @ 50% dilution	ASTM D1287	8.1
Equilibrium Boiling Point	ASTM D1120	171°C

Product Code: 6900

Date Issued: 23/10/2012

Date Superseded: 25/06/2012

Revision nr: 04