



Gulf Supreme Duty XLE 15W-40

Extra High Performance Diesel Engine Oil for Low Emission Engines

your local global brand

Product Description:

Gulf Supreme Duty XLE 15W-40 is an extra high performance diesel engine oil specially developed for use in modern, high-output, low emission engines meeting Euro IV & V & US 2007 on-highway exhaust emission standards. **Gulf Supreme Duty XLE 15W-40** not only addresses the unique needs of these new engines and enhances the life of exhaust after treatment devices but also provides improved protection to older engines. **Gulf Supreme Duty XLE 15W-40** is formulated with state-of-the-art additive technology and severely hydro processed base oils to provide outstanding performance and overall protection and exceeds the performance requirements of API CJ/SM service categories and is approved by major global OEMs like MAN, Volvo, Mack, Cummins etc.

Gulf Supreme Duty XLE 15W-40 has outstanding thermal- and oxidative stability that reduces low-temperature sludge build-up, high-temperature deposits and oil thickening. Excellent soot handling capability minimises soot related viscosity increase and leads to longer engine/oil life. Outstanding corrosive and abrasive wear protection extends life of engine components and superior shear stability maintains viscosity in severe high-temperature service and leads to improved wear protection. Exceptional TBN retention resists harmful effects of corrosive exhaust gases and extends oil life and low ash content reduces particulate build-up in Diesel Particulate Filter (DPF) and enhances its life.

Gulf Supreme Duty XLE 15W-40 is applicable for the latest high performance low emission engines including those equipped with DPFs and Exhaust Gas Recirculation (EGR) and meeting Euro IV & V & US 2007 on-highway exhaust emission standards. Also applicable for on-highway vehicles and off-highway equipments operating in severe low speed/heavy load conditions using ultra low (15 ppm) sulphur fuels and for high performance gasoline engines and mixed fleet operations requiring oils meeting API CI-4 PLUS, CI-4, CH-4, CG-4, CF-4, SM, SL and SJ performance levels.

Meets the specifications of:

ACEA E9/E7, Caterpillar ECF-3, ECF-2 & ECF-1a

Approved by:

API CJ-4/SM, MB-Approval 228.31, MAN M 3575, Mack EO-O Premium Plus
MTU Oil Category 2.1, DDC PGOS 93K218, Volvo VDS-4, Renault VI RLD-3, Cummins CES 20081

<u>Properties:</u>	<u>Test Methods:</u>	<u>Typical Values:</u>
SAE Viscosity Grade	SAE J300	15W-40
Density @ 15°C	ASTM D4052	881 kg/m ³
Kinematic Viscosity @ 40°C	ASTM D445	114 mm ² /s (cSt)
Kinematic Viscosity @ 100°C	ASTM D445	14.9 mm ² /s (cSt)
Low-Temperature Cranking Viscosity @ -20°C	ASTM D5293	<7000 mPa.s (cP)
Viscosity Index	ASTM D2270	136
Flash Point	ASTM D92	>215°C
Pour Point	ASTM D97	-36°C
Total Base Number	ASTM D2896	7.64 mgKOH/g
Sulphated Ash	ASTM D874	0.94 wt %

Product Code: 1533	Date Issued: 02/11/2012	Date Superseded: 28/09/2012	Revision nr: 04
--------------------	-------------------------	-----------------------------	-----------------